

Shenzhen Mary Photoelectricity Co., LTD

Address: No 19 Bldg, Nangang section, the third industrial zone,
tangtou block, shiyan town, baoan district, shenzhen china



Tel: +86-755-81791507

Fax: +86-755-81791520

www.mrled.cn

Date: 20/04/2011

P25 led strip curtain(1150USD/cabinet with Receiving card)

Display and Control Feature		Structure Feature	
Specification	Parameter	Specification	Parameter
Pixel Pitch	25mm	cabinet size	800 mm*800mm* 92mm
Pixel composing	1R1G1B 3 in 1	Display resolution/module	32 dots*32 dots
Wavelength (R)	625 ± 5	Physical resolution	1024 dots
Wavelength (G)	522 ± 3	Weight per	13.6 Kg/pcs
Wavelength (B)	567 ± 3	Transparent via panel	35%
Wave Angle (H)	120° (H) / 120° (V)	Install mode	Wallmount, hung and stand structure
Led package	SMD 5050		
Density	1600	Working Power	
Display color	256*256*256	Specification	Parameter
Whiteness brightness	≥ 3200cd	Working voltage	AC 220v/380v ± 10% 47~64Hz
Brightness level	256 grade	Max power	320W/pcs
Changing frame frequency	60 Hz	Average power	180-220W/pcs
Refresh	340 Hz	Short circuit protection	Yes
Driving method	Constant static	LED Chip	Silan
Control mode	synchronous	Working Environment	
Display port	DVI	Specification	Parameter
Display mode	1024*768 1024*1024	Environment	Indoor fix or outdoor rental
Out of control	1/10,000 (scattered)	Working temperature	--20~50°C
lifetime	100,000 hours	Working Humidity	10~90%